




| ROUND FL | UTED C | OLUMNS | | | |
|-----------|------------------|---------|---------------|---------|-------------------------|
| Size | Weight (lbs.) | Α | Dimensio B | ns C | *Centered Load Limit |
| 6" x 8' | 19 | 6" | 7-9/16" | 1-3/4" | 20,000 lbs. |
| 6" x 9' | 21 | 6" | 7-9/16" | 1-3/4" | 20,000 lbs. |
| 6" x 10' | 23 | 6" | 7-9/16" | 1-3/4" | 20,000 lbs. |
| 8" x 8' | 24 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 8" x 9' | 27 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 8" x 10' | 30 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 8" x 12' | 32 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 8" x 16' | 40 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 8" x 18' | 50 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 8" x 20' | 62 | 7-5/8" | 9-7/16" | 2-3/16" | 21,000 lbs. |
| 10" x 8' | 33 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 10" x 9' | 36 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 10" x 10' | 38 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 10" x 12' | 47 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 10" x 16' | 63 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 10" x 18' | 67 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 10" x 20' | 75 | 9-3/8" | 11-1/4" | 2-3/8" | 26,000 lbs. |
| 12" x 8' | 52 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 9' | 58 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 10' | 65 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 12' | 75 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 16' | 99 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 18' | 102 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 20' | 115 | 11-1/2″ | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 12" x 24' | 130 | 11-1/2" | 15-1/8" | 2-3/4" | 37,000 lbs. |
| 15" x 12' | 115 | 14-1/2" | 18-3/4" | 4-3/4" | 45,000 lbs. |
| 15" x 16' | 123 | 14-1/2" | 18-3/4" | 4-3/4" | 45,000 lbs. |
| 15" x 18' | 140 | 14-1/2" | 18-3/4" | 4-3/4" | 45,000 lbs. |
| 15" x 20' | 155 | 14-1/2" | 18-3/4" | 4-3/4" | 45,000 lbs. |
| 15" x 24' | 170 | 14-1/2" | 18-3/4" | 4-3/4" | 45,000 lbs. |
| 18" x 16' | 182 | 17-3/4" | 22-1/2" | 5″ | 45,000 lbs. |
| 18" x 18' | 198 | 17-3/4" | 22-1/2" | 5″ | 45,000 lbs. |
| 18" x 20' | 215 | 17-3/4" | 22-1/2" | 5″ | 45,000 lbs. |
| 18" x 24' | 247 | 17-3/4" | 22-1/2" | 5″ | 45,000 lbs. |
| 24" x 18' | 295 | 23-1/2" | 28-7/8" | 7-3/4" | 45,000 lbs. |
| 24" x 20' | 320 | 23-1/2" | 28-7/8" | 7-3/4" | 45,000 lbs. |
| 24" x 24' | 370 | 23-1/2" | 28-7/8" | 7-3/4" | 45,000 lbs. |

*Load-bearing capacity is dependent on distributing the load evenly over bearing surfaces of the shaft. All installation information is of general nature; columns should be installed and secured (fastened) according to standard construction practices and in compliance with applicable local, state and federal building regulations. Note: 2nd story balconies should not be attached directly to the side of any column.






- Load bearing
- Powder coat paint finish
- Available in four colors
- Cast aluminum capitals and bases
- Virtually maintenance free
- Class 1 Flame Spread classification
- Architectural fluting
- 6 SKUs packaged with capital & base in same box with column
- Common sizes ship within 48 hours
- Wraps around existing post (modification may be necessary)
- Ideal for commercial & residential applications



| SQUARE F | LUTED C | OLUMNS | | | |
|-----------------|------------------|-----------|-----------------|----------|-------------------------|
| Nominal Size | Weight (lbs.) | Α | Dimensions B | С | *Centered Load Limit |
| 3" x 8' | 8 | 3″ | N/A | N/A | 8,000 lbs. |
| 3" x 9' | 9 | 3″ | N/A | N/A | 8,000 lbs. |
| 4" x 8' | 16 | 3-1/2" | 5-5/8" | 1-7/8" | 12,000 lbs. |
| 4" x 9' | 18 | 3-1/2" | 5-5/8" | 1-7/8" | 12,000 lbs. |
| 4" x 10' | 20 | 3-1/2" | 5-5/8" | 1-7/8" | 12,000 lbs. |
| 6" x 8' | 24 | 5-1/2" | 8-1/2" | 2" | 23,000 lbs. |
| 6" x 9' | 27 | 5-1/2" | 8-1/2" | 2" | 23,000 lbs. |
| 6" x 10' | 30 | 5-1/2" | 8-1/2" | 2″ | 23,000 lbs. |
| 8" x 8' | 26 | 7-1/2" | 10-1/2" | 2" | 24,000 lbs. |
| 8" x 9' | 29 | 7-1/2" | 10-1/2" | 2" | 24,000 lbs. |
| 8" x 10' | 32 | 7-1/2" | 10-1/2" | 2" | 24,000 lbs. |
| 8" x 12' | 38 | 7-1/2" | 10-1/2" | 2″ | 24,000 lbs. |
| 10" x 8' | 41 | 10" | 12-7/8" | 2-11/16" | 26,000 lbs. |
| 10" x 9' | 46 | 10′ | 12-7/8" | 2-11/16" | 26,000 lbs. |
| 10" x 10' | 50 | 10″ | 12-7/8" | 2-11/16" | 26,000 lbs. |
| 10" x 12' | 59 | 10" | 12-7/8″ | 2-11/16" | 26,000 lbs. |
| 10" x 16' | 78 | 10″ | 12-7/8" | 2-11/16" | 26,000 lbs. |
| 10" x 18' | 88 | 10" | 12-7/8" | 2-11/16" | 26,000 lbs. |
| 10" x 20' | 98 | 10" | 12-7/8" | 2-11/16" | 26,000 lbs. |
| 12" x 8' | 49 | 11-15/16" | 15-1/8″ | 3-3/16" | 37,000 lbs. |
| 12" x 9' | 55 | 11-15/16" | 15-1/8″ | 3-3/16" | 37,000 lbs. |
| 12" x 10' | 60 | 11-15/16" | 15-1/8" | 3-3/16" | 37,000 lbs. |
| 12" x 12' | 71 | 11-15/16" | 15-1/8" | 3-3/16" | 37,000 lbs. |
| 12" x 16' | 92 | 11-15/16" | 15-1/8″ | 3-3/16" | 37,000 lbs. |
| 12" x 18' | 103 | 11-15/16" | 15-1/8" | 3-3/16" | 37,000 lbs. |
| 12" x 20' | 115 | 11-15/16" | 15-1/8" | 3-3/16" | 37,000 lbs. |



*Load-bearing capacity is dependent on distributing the load evenly over bearing surfaces of the shaft. All installation information is of general nature; columns should be installed and secured (fastened) according to standard construction practices and in compliance with applicable local, state and federal building regulations. Note: 2nd story balconies should not be attached directly to the side of any column.

All square shafts wrap-around existing posts without modification.

Features


- Load Bearing
- Powder Coat Paint Finish
- Available in Four Colors
- Cast Aluminum Capitals & Bases
- Virtually Maintenance Free
- Class 1 Flame Spread classification

- Architectural fluting
- 10 SKUs packaged with capital & base in same box with column
- Common sizes ship within 48 hours
- Wraps around existing post (modification may be necessary)
- Ideal for commercial & residential applications

Colors available:








| Wellington Columns | | | | | | 172 | |
|--------------------|------------------|--------|----------------|---------|--------|----------|-------------------------|
| Nominal Size | Weight (lbs.) | Α | Dimensior B | ns C | D | E | *Centered Load Limit |
| 6" x 8' | 25 | 5-1/2" | 8-1/2" | 2" | 3-1/2" | 9-5/8" | 12,000 lbs. |
| 6" x 9' | 28 | 5-1/2" | 8-1/2" | 2" | 3-1/2" | 9-5/8" | 12,000 lbs. |
| 6" x 10' | 31 | 5-1/2" | 8-1/2" | 2" | 3-1/2" | 9-5/8" | 12,000 lbs. |
| 8" x 8' | 27 | 7-1/4" | 9-7/8" | 3″ | 3-1/2" | 12-3/4" | 20,000 lbs. |
| 8" x 9' | 30 | 7-1/4" | 9-7/8" | 3" | 3-1/2" | 12-3/4" | 20,000 lbs. |
| 8" x 10' | 33 | 7-1/4" | 9-7/8" | 3″ | 3-1/2" | 12-3/4" | 20,000 lbs. |
| 8" x 12' | 27 | 7-1/4" | 9-7/8" | 3" | 3-1/2" | 12-3/4" | 20,000 lbs. |
| 9" x 8' | 45 | 9" | 11-11/16" | 3″ | 3-1/2" | 14-7/16" | 15,000 lbs. |
| 9" x 9' | 50 | 9" | 11-11/16" | 3″ | 3-1/2" | 14-7/16" | 15,000 lbs. |
| 9" x 10' | 55 | 9″ | 11-11/16" | 3″ | 3-1/2" | 14-7/16" | 15,000 lbs. |
| 9" x 12' | 65 | 9" | 11-11/16" | 3" | 3-1/2" | 14-7/16" | 15,000 lbs. |

^{*}Load-bearing capacity is dependent on distributing the load evenly over bearing surfaces of the shaft. All installation information is of general nature; columns should be installed and secured (fastened) according to standard construction practices and in compliance with applicable local, state and federal building regulations. Note: 2nd story balconies should not be attached directly to the side of any column.

Wellington available in white or primed.



- Load bearing
- Powder coat paint finish
- Prefinished matte, textured white or factory primed for paint
- Cast aluminum base with fabricated aluminum capital
- Aluminum, adjustable height astragal
- Virtually maintenance free
- Class 1 Flame Spread classification
- Common sizes ship within 48 hours
- Wraps around existing post (modification may be necessary)



Acadian

Deriving its heritage from the Deep South, the Acadian style column features an inset panel that is easily modified into multiple panels with optional, divider blocks.




Optional blocks shipped separately

| A CADIAN | Column | S | | | | |
|-----------------|------------------|--------|---|------------------------|-----|-------------------------|
| Nominal Size | Weight (lbs.) | Α | | Dimensions B | l c | *Centered Load Limit |
| 6" x 8' | 26 | 5-1/2" | • | 8-1/2" | 2" | 24,000 lbs. |
| 6" x 9' | 29 | 5-1/2" | , | 8-1/2" | 2" | 24,000 lbs. |
| 6" x 10' | 33 | 5-1/2" | • | 8-1/2" | 2" | 24,000 lbs. |
| 8" x 8' | 33 | 7-1/2″ | ' | 10-1/2" | 2" | 50,000 lbs. |
| 8" x 9' | 37 | 7-1/2" | , | 10-1/2" | 2" | 50,000 lbs. |
| 8" x 10' | 40 | 7-1/2″ | ' | 10-1/2" | 2" | 50,000 lbs. |
| 8" x 12' | 48 | 7-1/2" | | 10-1/2" | 2" | 50,000 lbs. |


*Load-bearing capacity is dependent on distributing the load evenly over bearing surfaces of the shaft. All installation information is of general nature; columns should be installed and secured (fastened) according to standard construction practices and in compliance with applicable local, state and federal building regulations. Note: 2nd story balconies should not be attached directly to the side of any column.

Acadian available in white or primed.



- Load bearing
- Powder coat paint finish
- Prefinished matte, textured white or factory primed for paint
- Cast aluminum capitals & bases
- Virtually maintenance free
- Class 1 Flame Spread classification
- Packaged with capital & base in same box with column
- Common sizes ship within 48 hours
- Wraps around existing post (modification may be necessary)





| Empire | Column | ıs | 1 | | |
|-----------------|------------------|--------|-----------------|--------|-------------------------|
| Nominal Size | Weight (lbs.) | Α | Dimensions B | С | *Centered Load Limit |
| 6" x 8' | 24 | 5-1/2" | 8-1/2" | 3-1/2" | 12,000 lbs. |
| 6" x 9' | 27 | 5-1/2" | 8-1/2" | 3-1/2" | 12,000 lbs. |
| 6" x 10' | 30 | 5-1/2" | 8-1/2" | 3-1/2" | 12,000 lbs. |
| 8" x 8' | 26 | 7-1/4" | 9-7/8" | 3-1/2" | 20,000 lbs. |
| 8" x 9' | 29 | 7-1/4" | 9-7/8" | 3-1/2" | 20,000 lbs. |
| 8" x 10' | 32 | 7-1/4" | 9-7/8" | 3-1/2" | 20,000 lbs. |
| 8" x 12' | 38 | 7-1/4" | 9-7/8" | 3-1/2" | 20,000 lbs. |
| 9" x 8' | 44 | 9″ | 11-11/16" | 3-1/2" | 15,000 lbs. |
| 9" x 9' | 49 | 9" | 11-11/16" | 3-1/2" | 15,000 lbs. |
| 9" x 10' | 54 | 9" | 11-11/16" | 3-1/2" | 15,000 lbs. |
| 9" x 12' | 64 | 9" | 11-11/16" | 3-1/2" | 15,000 lbs. |

*Load-bearing capacity is dependent on distributing the load evenly over bearing surfaces of the shaft. All installation information is of general nature; columns should be installed and secured (fastened) according to standard construction practices and in compliance with applicable local, state and federal building regulations. Note: 2nd story balconies should not be attached directly to the side of any column.

Empire available in white or primed.

- Load bearing
- Powder coat paint finish
- Prefinished matte, textured white or factory primed for paint
- Cast aluminum capitals & bases
- Virtually maintenance free
- Class 1 Flame Spread classification
- Common sizes ship within 48 hours
- Wraps around existing post (modification may be necessary)







Craftsman

The AFCO Craftsman column is the popular choice for any look that would incorporate a post porch design. These columns are great on a cottage or bungalow style residence, and with our premium white texture paint, never need any touch up maintenance.



| Craftsman Columns | | | | | |
|-------------------|------------------|--------|-----------------|--------|-------------------------|
| Nominal Size | Weight (lbs.) | Α | Dimensions B | l c | *Centered Load Limit |
| 6" x 8' | 18 | 5-1/2" | 6-3/4" | 2-1/2" | 20,000 lbs. |
| 6" x 9' | 20 | 5-1/2" | 6-3/4" | 2-1/2" | 20,000 lbs. |
| 6" x 10' | 22 | 5-1/2" | 6-3/4" | 2-1/2" | 20,000 lbs. |

*Load-bearing capacity is dependent on distributing the load evenly over bearing surfaces of the shaft. All installation information is of general nature; columns should be installed and secured (fastened) according to standard construction practices and in compliance with applicable local, state and federal building regulations. Note: 2nd story balconies should not be attached directly to the side of any column.

Craftsman available in white or primed.





- Load bearing
- Powder coat paint finish
- Prefinished matte, textured white or factory primed for paint
- Cast aluminum capitals & bases
- Virtually maintenance free
- Class 1 Flame Spread classification
- Common sizes ship within 48 hours
- Wraps around existing post (modification may be necessary)







Service Options

For **FIBERGLASS COLUMNS**, the following services are available:

- Round and square columns modified to wraparound an existing structural post. See chart below.
- Round and square columns cut to special lengths.
- Round columns cut at the bead to accommodate decorative capitals.
- Round columns cut to specified overall length to accommodate decorative capitals.

COLUMNS TO SURROUND STRUCTURAL SUPPORT

| Size | Inside Top Shaft Diameter | Largest Round Support | Largest Square Support | Column Type | Load Bearing Plate |
|------|---------------------------------|-----------------------------|------------------------------|----------------|--------------------------|
| 6" | 3-1/4" | 2-1/2" | 2-1/4" | Pro-Cast | Α |
| 8″ | 5-1/4" | 4-7/8" | 3-3/8" | Pro-Cast | В |
| 10" | 6-5/8" | 6-1/8" | 4-1/2" | Pro-Cast | В |
| 12" | 8-1/4" | 7-3/8" | 5-5/8" | Pro-Cast | E |
| 14" | 10-1/8" | 9-1/4" | 6-1/4" | Pro-Cast | N/A |
| 16" | 13" | 11-5/8" | 8-3/4" | Pro-Fusion | N/A |
| 18" | 13-5/8" | 12-1/2" | 9-1/2" | Pro-Fusion | N/A |
| 20" | 16-1/2" | 15-1/4" | 10-5/8" | Pro-Fusion | N/A |
| 22" | 17-1/4" | 16-1/8" | 11-3/8" | Pro-Fusion | N/A |
| 24" | 18" | 17-1/4" | 12-1/2" | Pro-Fusion | N/A |
| 30" | 25" | 22" | 16" | Pro-Fusion | N/A |
| 6" | 5" | 2" | 4" | Pro-Lite | Α |
| 8" | 7" | 5" | 6" | Pro-Lite | В |
| 10" | 9" | 7" | 8" | Pro-Lite | D |
| 12" | 11" | 9" | 10" | Pro-Lite | Α |
| 16" | 13-3/4" | 12" | 12" | Pro-Lite | |

| LOAD BEARING PLATE SIZE CODES | | | | | |
|-------------------------------|------|--|--|--|--|
| Size | Code | | | | |
| 7-3/16" x 7-3/16" | А | | | | |
| 7-7/8" x 7-7/8" | В | | | | |
| 9" x 9" | С | | | | |
| 9-5/8" x 9-5/8" | D | | | | |
| 10-3/4" x 10-3/4" | E | | | | |

For ALUMINUM COLUMNS, the following services are available:

- Round and square columns modified to wraparound an existing structural post. See chart below.
- Round and square shafts cut to specific lengths.

COLUMNS TO SURROUND STRUCTURAL SUPPORT

| | FLUTED A | UMINUM | | | |
|---|------------|--------------------------------|-----------------------------|------------------------------|--------------------------|
| | Size | No. of Staves Per Column | Largest Round Support | Largest Square Support | Load Bearing Plate |
| | 6" Round | 3 | 4-1/2" | 3-1/2" | Α |
| | 8" Round | 3 | 6-1/4" | 4-1/2" | С |
| | 10" Round | 4 | 7-3/4" | 6" | Е |
| | 12" Round | 5 | 9-3/4" | 7-1/2" | N/A |
| | 15" Round | 5 | 12" | 9" | N/A |
| | 18" Round | 6 | 15" | 11" | N/A |
| | 24" Round | 6 | 22" | 15" | N/A |
| | 4" Square | 2 | 3″ | 3″ | N/A |
| | 6" Square | 4 | 4-7/8" | 4-1/2" | В |
| | 8" Square | 4 | 6-7/8" | 6-1/2" | D |
| | 10" Square | 4 | 8-1/2" | 8-1/2" | E |
| | 12" Square | 8 | 10" | 10" | N/A |
| | WELLINGTO | ON A LUMIN | UM | | |
| | 6" | 4 | 4-7/8" | 4-1/2" | В |
| | 8" | 4 | 6-7/8" | 6-1/2" | D |
| | 9" | 4 | 8-7/8" | 7-1/4" | Е |
| | EMPIRE AL | .UMINUM | | | |
| | 6" | 4 | 4-7/8" | 4-1/2" | В |
| | 8" | 4 | 6-7/8" | 6-1/2" | D |
| | 9" | 4 | 8-7/8" | 7-1/4" | Е |
| | Acadian A | LUMINUM | | | |
| | 6" | 4 | 4" | 4" | Α |
| | 8" | 4 | 5-3/4" | 5-3/4" | D |
| | CRAFTSMA | N A LUMINL | М | | |
| H | 6" | 4 | 5-1/4" | 4-1/4" | N/A |
| | | | | | |

| LOAD BEARING PLATE SIZE CODES | | | | |
|-------------------------------|------|--|--|--|
| Size | Code | | | |
| 7-3/16" x 7-3/16" | А | | | |
| 7-7/8" x 7-7/8" | В | | | |
| 9" x 9" | С | | | |
| 9-5/8" x 9-5/8" | D | | | |
| 10-3/4" x 10-3/4" | E | | | |

FIBERGLASS COLUMNS

SHAFTS

 Pro-Cast and Pro-Lite shafts split for wrap-around applications. (charges apply)

NEW ITEM - REASSEMBLY KITS AVAILABLE

- Pro-Fusion large diameter column shafts custom built in two parts for wrap-around applications and pre-drilled for easy assembly.
- All Pro-Cast round and square pultruded column shafts feature optional cuts. (see chart below) (charges apply)
- All round and square shafts cut to specific length.
 (charges apply specific cut lengths available)
- Pro-Cast shafts cut to bead for decorative capitals.
- Shafts cut to overall length to accommodate decorative capitals. (charges apply)

CAPITALS


 Capitals may be split or cut to match column types. (charges apply to all)

ALUMINUM COLUMNS

- Round and square columns may be split for pilasters.
- Round and square columns may be modified for wrap-around installation.
- All shafts may be cut to specific length. (charges apply)
- All aluminum cap and base sets must be modified for wrap-around applications. (charges apply)

ALUMINUM & FIBERGLASS COLUMN CUTS

AFCO columns are available in the following plan types. Please specify when you order. Round and square column shafts, capitals and bases cut to meet special installation requirements. See chart below.



Only)